



GOODA-TH-1500NCL-Belt type Specifications-20200520

Item		Unit	Model
			TH-1500NCL
Cutting Capacity	Control Axis	No.	4
	Max.Milling Size (L*W*H)	mm	2 sides 40*1500*190/240 4sides 500*500*190/240
	Min.Milling Size (L*W*H)	mm	40*40*20
	One time Cutting Capacity	mm	2*2.0
Travel	X axis	mm	260
	Y axis	mm	260
	Z axis	mm	1750
Feed Speed	X/Y/Z Max. rapid feed rate	m/min	8
	Max.Cutting feed rate	m/min	8
	Manual feed speed	mm/min	1-1500
Spindle	Spindle speed	Rpm	50-500
	Spindle taper	-	NT50
	Cutter diameter	mm	200 OP 250
Motor	Spindle servo motor	Kw	2*9 OP 11



	X/Y axis feed servo motor	Kw	2.5
	Z axis feed servo motor	Kw	3
	Rotary table Servo motor	Kw	2
	Clamper hydraulic motor	Kw	2.25
Work table	Worktable dimension	mm	400*400+400*1000
	Max.Loading weight	Kg	2000
Hydraulic Clamper	Cylinder No.	Pcs	1 OP 3 OP 5
	Oil tank volume	L	80
Lubrication system	Lubricating oil tank	L	2*4
	Lubricating power	W	25
Floor space require (L*W*H)		mm	6.0*3.5*2.5
Machine weight		ton	16
CNC system			FANUC Oi-MF

● The information in this catalog are as of Jan.2020,and are subject to change without notice.

© GOODA MACHINERY MANUFACTURING CO.,LTD. All rights reserved.001 Jan.2020

www.goodacnc.com Email:sales@goodacnc.com Tel: +86 769 89760601 Tel: +86 769 81502791

No.137,Changdong Road, Changping Town, Dongguan city, GD, China