



GOODA-Gear type-TH-1600NCA-Specifications-20200520

Item		Unit	Model
			TH-1600NCA
Cutting Capacity	Control Axis	No.	4
	Max.Milling Size (L*W*H)	mm	1600*1600*440/490
	Min.Milling Size (L*W*H)	mm	420*420*20
	One time Cutting Capacity	mm	2*5.0
Travel	X axis	mm	660
	Y axis	mm	660
	Z axis	mm	2140
Feed Speed	X/Y/Z Max. rapid feed rate	m/min	8
	Max.Cutting feed rate	m/min	8
	Manual feed speed	mm/min	1-1500
Spindle	Spindle speed	Rpm	50-300
	Spindle taper	-	BT50
	Cutter diameter	mm	450 OP 500
Motor	Spindle servo motor	Kw	2*22 OP 30 OP 55
	X/Y axis feed servo motor	Kw	3



	Z axis feed servo motor	Kw	3
	Rotary table Servo motor	Kw	3
	Clamper hydraulic motor	Kw	2.25
Work table	Worktable dimension	mm	1100*1100
	Max.Loading weight	Kg	10000
Hydraulic Clamper	Cylinder No.	Pcs	1 OP 3 OP 5
	Oil tank volume	L	80
Lubrication system	Lubricating oil tank	L	2*4
	Lubricating power	W	25
Floor space require (L*W*H)		mm	7.0*8.0*2.65
Machine weight		ton	21
CNC system			FANUC 0i-MF

● The information in this catalog are as of Jan.2020,and are subject to change without notice.

© GOODA MACHINERY MANUFACTURING CO.,LTD. All rights reserved.001 Jan.2020

www.goodacnc.com Email:sales@goodacnc.com Tel: +86 769 89760601 Tel: +86 769 81502791

No.137,Changdong Road, Changping Town, Dongguan city, GD, China