



GOODA-TH-350NC-Belt type Specifications-20200520

Item	Unit	Model	
		TH-350NC	
Cutting Capacity	Control Axis	No.	4
	Max.Milling Size (L*W*H)	mm	350*350*140
	Min.Milling Size (L*W*H)	mm	20*20*20
	One time Cutting Capacity	mm	2*2.0
Travel	X axis	mm	200
	Y axis	mm	200
	Z axis	mm	600
Feed Speed	X/Y/Z Max. rapid feed rate	m/min	10
	Max.Cutting feed rate	m/min	10
	Manual feed speed	mm/min	1-1500
Spindle	Spindle speed	Rpm	50-500
	Spindle taper	-	NT50
	Cutter diameter	mm	150
Motor	Spindle servo motor	Kw	2*5.5
	X/Y axis feed servo motor	Kw	1.8
	Z axis feed servo motor	Kw	2
	Rotary table Servo motor	Kw	2
	Clamper hydraulic motor	Kw	1.5

Work table	Worktable dimension	mm	300*300
	Max.Loading weight	Kg	400
Hydraulic Clamper	Cylinder No.	Pcs	1
	Oil tank volume	L	60
Lubrication system	Lubricating oil tank	L	3
	Lubricating power	W	18
Floor space require (L*W*H)		mm	2.8*2.9*2.3
Machine weight		ton	6
CNC system			FANUC 0i-MF

- The information in this catalog are as of Jan.2020,and are subject to change without notice.
- © GOODA MACHINERY MANUFACTURING CO.,LTD. All rights reserved.001 Jan.2020

www.goodacnc.com Email:sales@goodacnc.com Tel: +86 769 89760601 Tel: +86 769 81502791

No.137,Changdong Road, Changping Town, Dongguan city, GD, China